



Fuji Silysia Chemical, LTD.

Fuji Silysia Chemical, LTD.
1000 Park Forty Plaza, Suite 420
Durham, NC 27713
Phone: 919-484-4158
Fax: 919-544-7769

MATERIAL SAFETY DATA SHEET

Contact: Fuji Silysia Chemical Ltd.
Address: 1000 Park Forty Plaza, Suite 420
Durham, NC 27713
Tel: 1-800-SYLYSIA / Fax: 252-413-0490
Manufacture: Fuji Silysia Chemical USA Ltd.
Address: 1215 Sugg Parkway Greenville, NC 27834
Tel: 252-413-0003 / Fax: 252-413-0490

SILICA GEL

Effective Date: January 1, 2013

1. Product Identification

Synonyms: Silica, Amorphous; Silicic Acid; Amorphous Silicon Dioxide

CAS No: 7631-86-9

Molecular Weight: 60.08

Chemical Formula: SiO₂

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent
Silica, Amorphous	7631-86-9	99.5 - 100%

3. Hazards Identification

Emergency Overview

AFFECTS RESPIRATORY SYSTEM. CAUSES IRRITATION TO EYES.

Potential Health Effects

Inhalation:

May cause dryness and irritation to mucous membranes, nose, and throat. Symptoms may include coughing, sore throat, dyspnea, wheezing, and non-specific chest illnesses.



Fuji Silysia Chemical, LTD.

Fuji Silysia Chemical, LTD.
1000 Park Forty Plaza, Suite 420
Durham, NC 27713
Phone: 919-484-4158
Fax: 919-544-7769

Ingestion:

No adverse effects expected.

Skin Contact:

May cause irritation with dryness and abrasion.

Eye Contact:

Causes irritation, redness, and pain.


Chronic Exposure:

Repeated exposure may cause symptoms similar to the effects on the above.

Aggravation of Pre-existing Conditions:

No information found.

NFPA Rating (Scale 0 – 4)



Health = 1
Fire = 0
Reactivity = 0

HMIS Rating (Scale 0 – 4)



Health = 1
Fire = 0
Reactivity = 0

4. First Aid Measures

Inhalation:

Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion:

Give several glasses of water to drink to dilute. If large amounts were swallowed, get medical advice.

Skin Contact:

Wash exposed area with soap and water. Get medical advice if irritation develops.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Information:

Use protective clothing and breathing equipment appropriate for the surrounding fire.



6. Accidental Release Measures

If its use requires manual handling, wear long sleeves and close-weave cotton glove with tight-fitting wristlets. Avoid formation of dust.

Keep away from ignition sources. Sweep up and containerize for reclamation or dispose.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. When pouring power into a container of flammable liquid, ground both containers electrically to prevent a static electric spark. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Amorphous Silica:

- OSHA Silica gel – PEL – $80\text{mg}/\text{m}^3$ /($\% \text{SiO}_2$)
- ACGIH Threshold Limit Value (TLV): 10 mg/m^3 (TWA) inhalable particulate; 3 mg/m^3 (TWA) respirable particulate.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators:

If its use requires manual handling, wear long sleeves and close-weave cotton gloves with tight-fitting wristlets. If dusty conditions prevail, use of an approved NIOSH/MSHA dust respirator is recommended. Wear goggles if dust causes eye discomfort

Skin Protection:

Wear protective gloves and clean body-covering clothing.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.



9. Physical and Chemical Properties

Appearance: Dry, white powder
Odor: Odorless.
Solubility: Insoluble in water.
Specific Gravity: 2.20
pH : 3.0-8.0
Boiling Point: 2230 deg. C
Melting Point : 1610 deg. C
Vapor Density (Air=1):No information found.
Vapor Pressure (mm Hg): 10 @ 1732 deg.C
Evaporation Rate (BuAc=1): No information found.

10. Stability and Reactivity

Stability:
Stable under ordinary conditions of use and storage.
Hazardous Decomposition Products:
No information found.
Hazardous Polymerization:
Will not occur.
Incompatibilities:
Hydrogen fluoride, fluorine, xenon hexafluoride, oxygen difluoride, and chlorine trifluoride.
Conditions to Avoid:
Heat, flame, ignition sources, dusting, moisture and incompatibles.

11. Toxicological Information

ANIMAL TOXICOLOGY:

TESTS FOR DOT HAZARD CLASSIFICATION:

1-hour LC50 (rat) > 2mg/l
48-hour Oral LD50 (rat) est. > 31,600 mg/kg
48-hour Dermal LD50 (rabbit) est. > 2,000 mg/kg
Not considered an ocular irritant.

TESTS FOR FDA APPROVAL FOR USE IN FOODS:

LD50 (mice) 8,000 mg/kg (limit of test)
LD50 (rats) 4,500 mg/kg (limit of test)
6 months² feeding tests (rats) at levels up to 10% of diet produced no effects.

-----Cancer Lists-----

Ingredient	IARC	Category
Silica, Amorphous	(7631-86-9)	3



12. Ecological Information

Environmental Fate : No information found.

Environmental Toxicity: No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Regulatory Information

U.S. Federal Regulations
WHMIS (Canada)

TSCA 8 (b) inventory: SILICA GEL
Not controlled under WHMIS (Canada)
CEPA DSL: SILICA GEL

International regulations
EINECS
DSCL (EEC)

SILICA GEL 231-545-4
R36/37/38-Irritating to eyes, respiratory system and skin.

International Lists

Australia (NICNAS): SILICA GEL
Japan (MITI): SILICA GEL
Korea (TCCL): SILICA GEL
Philippines (RA6969): SILICA GEL
China: No products were found

16. Other Information

Fuji Silysia Chemical Ltd. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. FUJI SILYSIA CHEMICAL LTD. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE



Fuji Silysia Chemical, LTD.

Fuji Silysia Chemical, LTD.
1000 Park Forty Plaza, Suite 420
Durham, NC 27713
Phone: 919-484-4158
Fax: 919-544-7769

**WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR
THE PRODUCT TO WHICH THE INFORMATION REFERS.
ACCORDINGLY, FUJI SILYSIA CHEMICAL LTD. WILL NOT BE
RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR
RELIANCE UPON THIS INFORMATION.**